

X-FREEZE 3402G

X-FREEZE 3402G, Engineered HPPE Shell, Brushed Acrylic Liner, Palm and 3/4 Back, Sandy Foam Nitrile Coated TPR Impact protection, Knitwrist, ANSI/ISEA 105, Cut A6, Touchscreen Fingertips.



Key Features & Benefits:

- ANSI A6 Cut Resistance for working with sharp or jagged materials.
- Sandy foam palm and 3/4 back provides exceptional wet and dry grip and additional warmth.
- Impact Level 2 Impact Rated for full coverage back of hand protection.
- Brushed Acrylic Terry Liner provides for comfortable and warm wear.
- Knitwrist helps prevent dirt, debris and cold weather from getting into the glove.
- Convenient Touchscreen Fingertips.

ANSI/ISEA 105



ANSI / ISEA 138



Applications:	Industries:	Certification/Ratings:
• Cold Weather Protection • Oil Rig Work • Machine Operations • Material Handling • Scaffolding	• Construction • Mining • Oil & Gas • Machinery/Equipment • Cold Climate Harsh Work	ANSI/ISEA-105 • Cut Level: A6 • Abrasion Level: 6 • Puncture Level: 4
		ANSI/ISEA-138 • Impact Level: 2
Ordering:	Composition:	Additional Information:
• Unit of Sale: 1 pr • Case Pack: 48 pr • Country of Origin: China • Available Sizes: MD -2XL	• Engineered HPPE Shell • Sandy Nitrile Palm & 3/4 Back • TPR Back of Hand • Knitwrist	Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/50°C. Air-dry or tumble-dry with no heat.  Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov

X-FREEZE 3402G

X-FREEZE 3402G, Engineered HPPE Shell, Brushed Acrylic Liner, Palm and 3/4 Back, Sandy Foam Nitrile Coated TPR Impact protection, Knitwrist, ANSI/ISEA 105, Cut A6, Touchscreen Fingertips.



Key Features & Benefits:

Item Number	Item Number UPC	Dozen UPC	Case UPC	Case L(in)	Case W(in)	Case H(in)	Weight (lbs)
3402GM	196852113095	40196852113093	50196852113090	11.8	26.0	13.0	28.7
3402GL	196852113101	40196852113109	50196852113106	11.8	26.0	13.0	29.8
3402GXL	196852113118	40196852113116	50196852113113	11.8	26.0	13.0	30.8
3402G2XL	196852113125	40196852113123	50196852113120	11.8	26.0	13.0	32.9

