

# X-SLASH 1140G

X-SLASH, Yellow, 10-Gauge Engineered Aramid Shell, Blue Crinkle Finish Latex Palm Coating, ANSI Cut A5, Heat Contact Level 2.



## Key Features & Benefits:

- ANSI A5 Cut Resistance for working with sharp or jagged materials.
- Provides Contact Heat Level 2 Resistance
- Crinkle Finish Latex provides grip in wet and dry conditions.
- Seamless Construction offers increased breathability and comfort.
- Elastic Knit Wrist helps prevent dirt and debris from entering the glove.
- ANSI Abrasion Level 4 and ANSI Puncture Level 4.

ANSI/ISEA 105



EN 388



| Applications:                                                                                                                                                            | Industries:                                                                                                                                                           | Certification/Ratings:                                                                                                                                                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• Waste Handling/Recycling</li> <li>• Material Handling</li> <li>• Glass Handling</li> <li>• Woodworking</li> </ul>               | <ul style="list-style-type: none"> <li>• Sanitation</li> <li>• Construction</li> <li>• Fishing Industries</li> <li>• Recycling</li> <li>• General Industry</li> </ul> | <b>ANSI/ISEA-105</b> <ul style="list-style-type: none"> <li>• Cut Level: <b>A5</b></li> <li>• Abrasion Level: <b>4</b></li> <li>• Puncture Level: <b>4</b></li> </ul>                           |
|                                                                                                                                                                          |                                                                                                                                                                       | <b>CE/EN407:2020,6.3 &amp; EN ISO 12127-1:2015:</b><br>Contact Heat Level: <b>2</b>                                                                                                             |
| Ordering:                                                                                                                                                                | Composition:                                                                                                                                                          | Additional Information:                                                                                                                                                                         |
| <ul style="list-style-type: none"> <li>• Unit of Sale: 1 dz</li> <li>• Case Pack: 6 pr</li> <li>• Country of Origin: China</li> <li>• Available Sizes: SM -XL</li> </ul> | <ul style="list-style-type: none"> <li>• 10-Gauge Engineered Aramid Shell</li> <li>• Crinkle Finish Latex Palm</li> <li>• Knitwrist</li> </ul>                        | Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/50°C. Air-dry or tumble-dry with no heat.                                                         |
|                                                                                                                                                                          |                                                                                                                                                                       |  Warning: Cancer & Reproductive Harm-<br><a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

# X-SLASH 1140G

X-SLASH, Yellow, 10-Gauge Engineered Aramid Shell, Blue Crinkle Finish Latex Palm Coating, ANSI Cut A5. Heat Contact Level 2.



## Key Features & Benefits:

| Item Number | Item Number UPC | Dozen UPC | Case UPC       | Case L(in) | Case W(in) | Case H(in) | Weight (lbs) |
|-------------|-----------------|-----------|----------------|------------|------------|------------|--------------|
| 1140GS      | 196852108176    |           | 50196852108171 | 21.3       | 11.8       | 11.8       | 17.9         |
| 1140GM      | 196852108183    |           | 50196852108188 | 21.3       | 11.8       | 11.8       | 17.9         |
| 1140GL      | 196852108190    |           | 50196852108195 | 21.3       | 11.8       | 11.8       | 17.9         |
| 1140GXL     | 196852108206    |           | 50196852108201 | 21.3       | 11.8       | 11.8       | 17.9         |

