



X-SPLASH 7000D

X-SPLASH 7000D. Microporous Coverall with Collar, Open Wrists & Ankles



Key Features & Benefits:

- Breathable, Durable, Comfortable and Affordable Microporous Coveralls.
- Provides all day protection from particulates, some liquids and aerosols.
- Attached Collar, Open Wrists and Ankles.
- Easy to take on and off, Zipper Closure, and Surged Seams

Applications:		Industries:	Certifications/Ratings:	
• Asbestos/Lead Abatement • Spill Cleanup • Mold Remediation • Food Processing • Painting		• Pharmaceutical • Agriculture • Environmental • Sanitation • Construction	ASTM D5034-21 (Grab Method) • Warp/Length lbf 20.6 • Weft/Width lbf 14.0 ASTM D5733-99 • Warp/Length lbf 10.0 • Weft/Width lbf 5.6	
Ordering:		Composition	Certifications/Ratings:	
• Unit of Sale- 1 CS • Case pack- 25 EA • Country of Origin- Bangladesh • Available Sizes M-5XL		• 100% Microporous Component Materials Comply with all FFDCA Guidelines for Food Contact, 21 CFR Parts 170-199	ASTM D3776/D3776M-20, OPT C • Weight oz/yd² 1.4 • Weight g/m² 48	
		 Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov	EN 1149-5:2018, Clause 4.2.1 Electrostatic Material Requirements - PASS	



X-SPLASH 7000D

X-SPLASH 7000D. Microporous Coverall with Collar,
Open Wrists & Ankles

Packaging Dimensions

	X-Small	Small	Medium	Large	X-Large	2X-Large	3X-Large	4X-Large	5X-Large
Chest	20.5 (52.1)	22.0 (55.9)	23.5 (59.7)	25.0 (63.5)	26.5 (67.3)	28 (71.1)	29.5 (74.9)	31.3 (79.0)	31.88 (81.0)
Inseam	26.5 (67.3)	27.52 (69.9)	28.0 (71.1)	29.0 (73.7)	29.5 (74.9)	30.5 (77.5)	31.5 (80.0)	33.5 (80.0)	34.3 (87.0)
Sleeve Outseam	29.0 (73.7)	31 (78.7)	32.5 (82.6)	33.5 (85.1)	35.0 (88.9)	36.5 (92.7)	37.0 (94.0)	38.2 (97.0)	39.4 (100)
Body Length	31.0 (78.7)	33.0 (83.8)	35.0 (88.9)	37.0 (94.0)	38.5 (97.8)	40.5 (102.9)	42.5 (108.0)	44.1 (112)	45.7 (116)
Sleeve Opening	5.5 (14.0)	5.5 (14.0)	6.0 (15.2)	6.0 (15.2)	6.0 (15.2)	6.0 (15.2)	6.5 (16.5)	7.1 (18.0)	7.48 (19.0)
Leg Opening	9.5 (24.1)	9.5 (24.1)	10.0 (25.4)	10.0 (25.4)	10.0 (25.4)	10.0 (25.4)	10.5 (26.7)	11.0 (28.0)	11.4 (29.0)
Front Opening	21.5 (54.6)	21.5 (54.6)	25.5 (64.8)	25.5 (64.8)	25.5 (64.8)	27.5 (69.9)	27.5 (69.9)	79.1 (24.0)	30.7 (78.0)

Resistance of Materials Used in Protective Clothing to Penetration by Liquids

ASTM F903-18, Procedure: Procedure D

Sodium Hydroxide, 50%

Observation on Viewing Side

0 psig (0kPa) for 1 minute Pass

Sodium Hypochlorine, 10%

Observation on Viewing Side

0 psig (0kPa) for 1 minute Pass

PACKAGING SPECIFICATIONS

ITEM# 7000D



X-SPLASH 7000D

X-SPLASH 7000D. Microporous Coverall with Collar, Open Wrists & Ankles

Packaging Dimensions

Item Number	Item Number UPC	Inner UPC	Case UPC	Case L (In)	Case W (In)	Case H (In)	Weight (lbs)
7000DM	196852107636		196852107636	14.17	10.63	14.17	9.46
7000DL	196852107643		196852107643	14.17	10.63	14.17	9.90
7000DXL	196852107650		196852107650	14.17	10.63	14.17	10.34
7000D2XL	196852107667		196852107667	14.17	10.63	14.17	11.00
7000D3XL	196852107674		196852107674	14.17	10.63	15.75	11.88
7000D4XL	196852107681		196852107681	14.17	10.63	15.75	12.98
7000D5XL	196852107698		196852107698	14.17	10.63	16.54	13.42



www.C2VPPE.com