

# X-STRESS 2405G

X-STRESS, Gray, 13-Gauge Polyester Shell, Dual Coating-Flat Nitrile under Fully Coated Black Sandy Nitrile, Touchscreen Fingertips, Sanitized®.



## Key Features & Benefits:

- Seamless knit 13 gauge polyester construction provides comfort and dexterity.
- Fully coated with Sandy Nitrile this product offers maximum abrasion resistance, and overall hand protection for longer lasting wear in harsh, oily and/or wet conditions
- Full dual coating makes the glove more resistant to chemicals, water and ultraviolet light.
- Elastic Knit Wrist helps prevent dirt and debris from entering the glove.
- Touchscreen Fingertips
- Sanitized®
- ANSI Abrasion Level 4, Puncture Level 2.

ANSI/ISEA 105



EN 388



| Applications:                                                                                                                                                             | Industries:                                                                                                                                                       | Certification/Ratings:                                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• Fastening</li> <li>• Parts &amp; Materials Assembly</li> <li>• Maintenance &amp; Repair</li> <li>• Parts Cleaning</li> </ul>     | <ul style="list-style-type: none"> <li>• Automotive</li> <li>• Electronics</li> <li>• Janitorial</li> <li>• Metal Fabrication</li> <li>• Plumbing/HVAC</li> </ul> | <b>ANSI/ISEA-105</b> <ul style="list-style-type: none"> <li>• Cut Level: <b>X</b></li> <li>• Abrasion Level: <b>4</b></li> <li>• Puncture Level: <b>2</b></li> </ul> |
|                                                                                                                                                                           |                                                                                                                                                                   | <b>ANSI ISEA - 138</b><br>Impact Level: <b>NR</b>                                                                                                                    |
| Ordering:                                                                                                                                                                 | Composition:                                                                                                                                                      | Additional Information:                                                                                                                                              |
| <ul style="list-style-type: none"> <li>• Unit of Sale: 1 dz</li> <li>• Case Pack: 12 dz</li> <li>• Country of Origin: China</li> <li>• Available Sizes: SM-2XL</li> </ul> | <ul style="list-style-type: none"> <li>• 13 Gauge Polyester/Elastic Shell</li> <li>• 2-Layer Nitrile Fully Coated.</li> <li>• Knitwrist</li> </ul>                | Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/50°C. Air-dry or tumble-dry with no heat.                              |
|                                                                                                                                                                           |                                                                                                                                                                   | Warning: Cancer & Reproductive Harm-<br>www.P65Warnings.ca.gov                                                                                                       |

# X-STRESS 2405G

X-STRESS, Gray, 13-Gauge Polyester Shell, Dual Coating-  
Flat Nitrile under Fully Coated Black Sandy Nitrile,  
Touchscreen Fingertips, Sanitized®.



## Key Features & Benefits:

| Item Number | Item Number UPC | Dozen UPC | Case UPC       | Case L(in) | Case W(in) | Case H(in) | Weight (lbs) |
|-------------|-----------------|-----------|----------------|------------|------------|------------|--------------|
| 2405GS      | 196852107506    |           | 50196852107501 | 20.9       | 11.0       | 12.6       | 18.0         |
| 2405GM      | 196852107513    |           | 50196852107518 | 20.9       | 11.0       | 12.6       | 19.5         |
| 2405GL      | 196852107520    |           | 50196852107525 | 20.9       | 11.0       | 12.6       | 20.0         |
| 2405GXL     | 196852107537    |           | 50196852107532 | 20.9       | 11.0       | 12.6       | 20.5         |
| 2405G2XL    | 196852107544    |           | 50196852107549 | 20.9       | 11.0       | 12.6       | 21.0         |

